

5 APPARATUS FOR PICKING UP PHYSIOLOGICAL DATA OF AT LEAST ONE  
PERSON IN A VEHICLE

10 ~~Background Information~~ Field of the Invention

The present invention ~~is based on~~ provides an apparatus for picking up physiological data of at least one person in a vehicle, ~~as generically defined by the preamble to the independent claim.~~

15 ~~Summary of the Invention~~ Summary

20 The apparatus of the present invention for picking up physiological data of at least one person, ~~having the characteristics of the independent claim,~~ has the advantage that the apparatus is configured such that on the basis of the physiological data, it performs a determination of the age of the at least one person. Thus ~~in particular,~~ it is possible to activate such restraint devices as air bags and belt  
25 tighteners in a way adapted to the situation. Since the bones of a human being become more fragile with age, it is advantageous for the air bag in the event of a crash, if an older person is detected, to be blown up less powerfully than for a younger person. Bone flexibility in people over 50 is  
30 only approximately 30% of the bone flexibility of 25-year-olds. When the belt tighteners are tripped, the ribs of older passengers may be broken, and there is the risk of internal bleeding if the belt force limiter is not immediately switched

on.

Besides its use in vehicles, the apparatus of the present invention may also be employed for instance in age-dependent access release devices or age-dependent dispensing of consumer goods.

However, the apparatus of the present invention ~~develops its greatest advantages in~~ is explained herein in the context of use in the vehicle.

~~By the provisions and refinements recited in the dependent claims, advantageous improvements to the apparatus recited in the independent claim for picking up physiological data of at least one person are possible.~~

It is especially advantageous that the at least one sensor, which is used for picking up the physiological data, is embodied as an image transducer. A video sensor, in particular a stereo video sensor, is used, which by triangulation is capable of determining the spacing of the person from an air bag cover and in particular of determining his pupil size. To that end, an evaluation module which is configured for measuring the pupil size is associated with the image transducer or video sensor. From the pupil size, it is simple to draw a conclusion about the age of the applicable person. It is known that the pupil size decreases with age. In the elderly, it may shrink to as little as one-third its youthful size.

Instead of the stereo video sensor, still other methods are

conceivable that combine a video sensor with a spacing measurement. For spacing measurement, other methods may be used for triangulation, for instance using structured lighting or transit time processes, such as LIDAR, imaging LIDAR, radar or ultrasound, or interferometry methods, in other words spacing measurement on the basis of the phase displacement of two laser beams on the basis of their different light travel distances.

Advantageously, the apparatus of the present invention may combine the image transducer with further sensors, in order either to obtain other data for triggering the restraint devices adaptively to the situation or to correlate the pupil size with other physiological data, in order to put the age determination on a better basis. To that end, it is for instance possible, from the image signal ~~or in other words in particular the~~, e.g., video signal, to evaluate the hair color and/or smoothness of the face and/or skin texture. A classifier may also be trained to assign the persons to various age classes on the basis of the image signal.

The measured values alone may give a false impression of the age of the person, but in correlation, ~~particularly~~ with the pupil size, for example, these parameters are capable of making the age determination more reliable.

As further measured values, the pulse rate, which is ascertained by a pressure pickup, or electrical parameters, such as the electrical resistance of the skin or a capacitance measurement to determine the proportion of water in the body, may be used. The proportion of water in the body also

indicates a variable age in a person, since the proportion of water in older persons drops to 60% of the body weight, compared to 90% in children.

5 It is furthermore advantageous if the apparatus of the present invention employs measured values from a weight measurement of the person in order to draw a conclusion about the age of that person. The weight measurement may be performed with a mat on the seat or with force measuring pins or other sensors for  
10 determining the mass.

#### Drawing Brief Description of the Drawings

~~Exemplary embodiments of the present invention are shown in~~  
15 ~~the drawing and will be explained in further detail in the~~  
~~ensuing description.~~ Figure 1 shows a block circuit diagram of the apparatus of the present invention, and.

Figure 2 shows a ~~configuration~~ schematic illustration of the  
20 apparatus of the present invention in the vehicle.

#### Description Detailed Description

Particularly with the introduction of front-passenger air  
25 bags, the necessity has arisen, for reasons of safety and insurance, of detecting a front-passenger seat occupied by a person. In an accident, if that seat is not occupied, no passenger needs protection, and it would therefore entail unnecessarily high repair costs if the air bag were to be  
30 deployed. Seat occupation detection for detecting a person is widely employed for this purpose. Some ideas for automatic

detection of a child seat also already exist.

According to the present invention, the apparatus for picking up physiological data is now configured in such a way that it becomes possible to determine the age of the passenger, that is, the person in the vehicle. However, the apparatus of the present invention may also be employed outside the vehicle. Inside the vehicle, however, determining the age in the event of an accident makes it possible to activate the restraint devices in a way adapted to the situation and the persons involved.

Analyzing the size of the pupils of a person, ~~in particular~~ e.g., by an image transducer such as a video system, and combining this information with other measured values independent of it, makes it possible to determine the age of a person. Especially since the size of the pupils decreases sharply with age, this is a good parameter for detecting an older person. The following table shows how the pupil cross section decreases with increasing age.

Age (years)	Day (mm)	Night (mm)	Difference
20	4.7	8.0	3.3
30	4.3	7.0	2.7
40	3.9	6.0	2.1
50	3.5	5.0	1.5
60	3.1	4.1	1.0
70	2.7	3.2	0.5

80	2.3	2.5	0.2
----	-----	-----	-----

Table 1: Pupil diameter in persons of various ages

Thus, according to the present invention, the targeted  
5 protection of older persons in a car accident becomes  
possible. This protection of older persons is much more  
important than detecting their sex, since for instance women  
who are not pregnant withstand higher accelerations and  
pressures per unit of surface area than men of the same age,  
10 and consequently do not require air bag protection until at  
higher impact speeds.

Especially with the aid of a stereo video sensor, by  
triangulation, it is possible to ascertain the spacing of the  
15 passenger from the air bag cover and the size of the pupils of  
a person. Alternatively, the size of the pupils may be  
ascertained with a video camera in combination with an  
ultrasound spacing sensor. In both cases, it is ~~decisive~~  
provided to focus on the eyes of the person with the video  
20 system and follow them and measure their size at certain  
intervals. The brightness in the vehicle may be estimated on  
the basis of known areas in the vehicle, such as the vehicle's  
headlining. An estimate of the age may be made with the aid  
of the brightness in the vehicle and the size of the pupils.  
25 Chronological filtering ~~increases the invulnerability~~  
minimizes the inaccuracy of this age estimate to brief  
fluctuations in brightness. For persons who wear glasses, the  
size of the pupils may still be determined relatively  
accurately despite the distortion, for instance if the size of  
30 the eye and the iris are used as a reference and the

distortion from the glasses is eliminated by reverse calculation.

The apparatus according to the present invention ~~develops its greatest advantages when~~ may also provide that the measurement

5 of the pupil size for estimating the age is combined with other measured values in order to obtain redundancy and greater certainty in the determination. These additional measured values may on the one hand originate in the same video system, examples being the hair color, deep wrinkles in  
10 the face, circles under the eye, or the texture of the skin. However, these measured values may also originate in other sensor systems. For instance, this may involve measuring the pulse of the vehicle driver, using pressure sensors in the steering-wheel rim. In older persons, the pulse is slower  
15 than in younger persons. As the pressure pickup, piezoelectric sensors may also be used, disposed for instance in the seats.

Measuring the properties of the hands may be done for the  
20 driver using sensors for measuring the electrical resistance, that is, the skin resistance between defined spacings, ~~such as~~ e.g., 2 cm, for measuring the temperature, and for measuring the distribution of contact pressure on the steering-wheel rim. In this way as well, it is possible to generate at least  
25 one indicator of the age of the person ~~involved~~ measured.

A further ~~possible way~~ embodiment is to detect the displacement currents, that is, the capacitance between transmitting and receiving electrodes in the seat, in an  
30 electrical field. For a passenger detected with the video system, for instance, the proportion of water in his body may

be determined from the measurement of capacitance. A lesser capacitance in the electrical field means a lesser proportion of water and is thus an indication of an older person, since the proportion of water in older persons usually amounts to  
5 only 60%, compared to 90% in children.

With a video system for determining the stature of a passenger and an absolute weight sensing system, for instance using a force measuring pin in the seat height adjusting linkages or  
10 between the seat rail and seat rocker, the proportion between passenger weight and passenger stature may be ascertained. If this proportion is below a limit value, still another indication of an older person is obtained.

15 Measuring the pupil size, however, ~~is~~ may be the most important building block in determining the age. However, the pupils may atypically be dilated for several hours from the effect of medication, for instance after an examination of the retina made by an ophthalmologist. Measuring the pupils alone  
20 would then lead to an incorrect result, with unwanted, adverse consequences to old passengers if the passenger protection is activated in the event of a crash.

For reliable anthropometric and nonintrusive determination of  
25 age, it is therefore necessary also to take into account the inputs of the aforementioned further sensors, or some of these sensors.

Figure 1 shows a block diagram of the apparatus of the present  
30 invention ~~in a block circuit diagram~~. An image transducer 1 is connected to an evaluation module 2 via a data output.

Evaluation module 2 is connected to a first data input of a control unit 3, which includes a processor. A weight sensor 6, which determines the weight of a vehicle passenger in the seat, is connected to a second data input of control unit 3.

5 This weight sensor is a force measuring pin, which is disposed in the seat height adjusting linkages. Control unit 3 serves to trigger restraint devices, so that control unit 3 is connected to restraint devices 4 via one data output. Via a third data input, control unit 3 is connected to crash ~~sensors~~  
10 sensor system 5, for detecting a crash. Besides inertial sensors, precrash sensors or deformation sensors may be present in crash sensor system 5. Besides weight sensors 6, which may also be embodied as a mat on the seat, still other sensors are possible, for instance for picking up the pulse of  
15 the person or electrical sensors for determining the skin impedance or capacitance of the person involved. Image transducer 1 is embodied here as a stereo video sensor, ~~in order which,~~ by triangulation, ~~to determine~~ determines the pupil size of the person involved and that person's spacing  
20 from an air bag cover. This calculation is performed in particular by evaluation module 2, embodied here as a microcontroller. Module 2 may also be disposed in control unit 3 itself, and for instance may also simply be software in a central processor in control unit 3.

25 By image transducer 1 and optionally further sensors, as described above, control unit 3 determines the age of the applicable person. In the event of a crash, control unit 3 will then trigger the applicable air bag or belt tightener to  
30 suit the age of the person, as a function of this age determination.

Figure 2 shows a configuration of the apparatus of the present invention in the vehicle. Identical components as those shown in Fig. 1 again have the same reference numerals. Image

5 transducer 1 is connected via the data output to evaluation module 2, which in turn is connected to a first data input of control unit 3. A weight sensor 7 is connected to a second data input of control unit 3 and is located in a seat cushion 9 of a vehicle seat. A pressure pickup 8 is connected to a  
10 third data input of control unit 3 and is intended for measuring the pulse rate of the driver seated on the seat. A pressure sensor 12 is connected to a fourth data input of control unit 3, so as to measure the driver's pulse at steering wheel 11. An impedance measuring instrument 13 is  
15 also disposed in steering wheel 11, and it is connected to a fifth data input of control unit 3 in order to determine the impedance of the skin. Further sensor types already named above may be employed here. It is also possible to use fewer sensors than those described here. Sensors may also be built  
20 into backrest 10 of the seat. In particular, an ultrasound spacing meter may be employed here.

Abstract

ABSTRACT

An apparatus for determining physiological data is distinguished in being suitable provided for determining age  
5 of a vehicle passenger in the context of safety apparatus deployment. For picking up the physiological data, a sensor is used. In particular, the apparatus is configured for measuring the pupil size, which is a good parameter for distinguishing age. Preferably, ~~this parameter is~~ This  
10 parameter may be correlated with further measured values, in order to put the age determination on a reliable basis.

~~(Figure 1)~~

15